

CECOR fresh Coolant Dispensers distribute clean coolant to machine tools. Use plant air supply for the DA5 series. Use single phase electric for DE10 series. Gravity Dispenser DX-110PL provides an easy way to dispense coolant and oil without a power source.

- **DA5 and DE10 available in 90, 140 and 175 gallon capacity. DX-110PL has a 110 gallon tank.**
- **Air unit discharge rate to 25 gpm, electric unit discharge rate to 23 gpm.**
- **Loads through fill-hatch or suction pump-in.**
- **Automatic Overfill Protection.**
- **Safe, easy one-person handling.**



DE10-175PT Coolant Dispenser

Paired with a CECOR Coolant Sumpcleaner becomes a two-unit system for collection and delivery cycle.



DX-110PL

CECOR Gravity Dispenser DX-110PL

Gravity Dispenser DX-110PL is a low-cost option for dispensing coolant and oil without a power source. Plastic polyethylene tank empties through a plastic hose fitted with a full flow nozzle or by a faucet drain located in the base.

- Liquid level visible through translucent tank.
- Capacity: 110 gallons
- Gallon markings on tank.
- Mounted on two swivel and two rigid 8" casters with poly tires.
- Channel construction for secure fork lift entry.
- Shipping weight: 462 lbs.

Powered Coolant Dispensers

Tank Size: 90, 140 and 175 gallon capacity

Pumping Rate: 25 gpm - Air Series
23 gpm - Electric Series

Pump: **(Electric Unit)-DE10**
1 HP Electric Motor driving rotary vane-type air pump
Volts 115
Amps 13.4
Hertz 60
Phase 1

Discharge: 53 - 80 CFM.

Tank: Heavy gage steel with push handle and tow bar. Convenient liquid level indicator. 6" fill hatch. Bottom drain plug.

15' electric power cord

Transport: Mounted on two 12" x 3" poly wheels and one 8" x 3" poly caster. Durable poly wheels are resistant to oil and chips. Roller bearing wheels for easy one-person handling.

(Air Unit)-DA5
Air operated vacuum/pressure unit creates regulated light pressure for easy flow discharge.

Spill Prevention: Automatic overfill control. All discharge ports valved.

20' oil resistant air supply hose.

Hose: 1-1/4" I.D. x 16' oil-resistant PVC dispensing hose with full-flow shut-off nozzle.

Requirements: 1/2" air service with line pressure of 75 to 120 psi.

Model Number	Tank Size	Transport	Wheels	Dimensions	Shipping Weight
DE10-90PT	90 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 30" wide 48" high	580 lbs.
DE10-140PT	140 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 34" wide 54" high	620 lbs.
DE10-175PT	175 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	74" long 34" wide 54" high	735 lbs.
DA5-90PT	90 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 30" wide 51" high	470 lbs.
DA5-140PT	140 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 34" wide 57" high	510 lbs.
DA5-175PT	175 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	74" long 34" wide 57" high	625 lbs.
DX-110PL	110 gallons	Push bar, front end bumpers	Two swivel and two rigid 8" casters with poly tires.	54" long 31" wide 52" high	462 lbs.



CECOR

102 Lincoln St.
Verona, WI 53593
1-800-356-9042

Fax: 608-845-6792
cecor@cecor.net
www.cecor.net