

Use CECOR's SE10 single phase electric Sumpcleaner/Filter anywhere in the plant.

- Available in 90, 140, 175, 300, 400, 500 and 600 gallon capacity.
- Pumping rate to 60 gallon per minute.
- Generates suction to 17" Hg (Mercury) or 231" water.
- 115/60/1 electricals
- Efficient 1 Horsepower electric motor.

The SE10 Sumpcleaner/Filter is also available as a Combination Sumpcleaner/Filter and Coolant Dispenser.

**Caution:** Machines must not be used for flammable fluids (fuels, paints, solvents, etc.) . Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc.) .



SE10-90PT Sumpcleaner/Filter.



Standard F10 Filter

## F10 - 1.0 Cubic Foot Filter

The F10 strainer basket and fabric liner has a capacity of 1.0 cubic foot and is standard on the SE10. The reusable filter has built in grips and is small enough for one person to lift. Course, fine and polypropylene filter bags are standard with the F10 filter basket.



Optional F23 Filter

## F23 - 2.3 Cubic Foot Filter (Optional)

With a 2.3 cubic foot capacity, the F23 filter is fitted for fork lift or hook hoist handling. Patented compound linkage and rotary latch controls the bottom opening door for safe emptying. The filter assembly comes complete with a polypropylene filter sleeve. The F23 filter is optional on the SE10. Optional fine weave polypropylene filter sleeve available.



SE10-175PL6 Sumpcleaner/Filter.

- Pump:** Rotary, vane-type vacuum pump
- Pumping Rate:** Up to 60 gallons per minute.
- Suction Lift:** 17" Hg (Mercury) or 231" water
- Pressure Discharge:** 6 PSI (pounds per square inch) with safety backup valve.
- Filter:** F10 Filter has 1 cubic foot capacity and is standard on the SE10. Optional F23 (2.3 cubic feet) capacity is recommended when coolant is loaded with chips and swarf.
- Spill Prevention:** Automatic overflow protection. All discharge ports are valved.
- Hose:** 1 1/2" I.D. x 16' oil-resistant PVC suction/discharge hose including quick-disconnect couplers and suction tools.
- Cleaning Tools:** Flared Nozzle  
Flexible Nozzle  
Straight Nozzle
- Power Cord:** 15 feet standard  
50 feet available

- Tank Size:** 90, 140, 175, 300, 400, 500 and 600 gallon capacity.
- Motor:** 1 HP Electric Motor  
Volts 115  
Amps 13.4  
Hertz 60  
Phase 1

See page 33 for information on base options

**Options**

Model Number	Tank Size	Cleanout Door	Transport	Wheels	Dimensions	Shipping Weight	TW Base	PL6 Base	PLM Base	CB1 Base	CB2 Base	CB3 Base	CB4 Base	CB5 Base	F23 Filter	Floor Squeegee	
SE10-90PT	90 gallon	8" x 10" with a 1 1/2" drain port	PT Base for push or tow transport.	Two 12" x 3" poly wheels and one 8" x 3" poly caster	68" long 30" wide 48" high	650 lbs.	X	X	X	X	X	X	X	X	X	X	
SE10-140PT	140 gallon				68" long 34" wide 54" high	690 lbs.	X	X	X	X	X	X	X	X	X	X	X
SE10-175PT	175 gallon				80" long 34" wide 54" high	805 lbs.	X	X	X	X	X	X	X	X	X	X	X
SE10-300TW	300 gallon	16" diameter with hinged door with a 2 1/2" drain port.	TW Base - Tow Bar with pintle-eye hitch to accommodate most in-plant tugs or tractors.	Mounts two heavy-duty 16" x 4" wheels and one 12" x 3" swivel casters.	96" long 40" wide 62" high	1085 lbs.	S	NA	X	X	X	X	X	X	X	X	
SE10-400TW	400 gallon				99" long 46" wide 68" high	1490 lbs.	S	NA	X	X	X	X	X	X	X	X	X
SE10-500TW	500 gallon				111" long 48" wide 70" high	1503 lbs.	S	NA	X	X	X	X	X	X	X	X	X
SE10-600CB1	600 gallon				CB1 Base -Custom base for mounting on trailer or truck.	Not applicable	121" long 42" wide 60" high	1669 lbs.	NA	NA	NA	X	X	X	X	X	X

NOTE: Engineering Specifications subject to change without notice.



**CECOR**

102 Lincoln St. Verona, WI 53593 1-800-356-9042  
Fax: 608-845-6792 cecor@cecor.net www.cecor.net

**X = Available**  
**S = Standard**  
**NA = Not Available**