

*The Extra Power Sumpcleaner is recommended for fast removal of coolants and solids in large operations. Five horsepower electric motor powers fast removal of coolant and solids from machine tools. Large capacity filter holds five cubic feet of solids.*

- Available in 175, 300, 400, 500 and 600 gallon capacity.
- Pumping rate to 110 gallons per minute.
- Generates suction to 13" Hg (Mercury) or 177" water.
- 208-230-460/60/3 electricals.
- Large capacity filter
- Five Horsepower electric motor.

*The Extra Power unit is also available as a Combination Sumpcleaner/ Filter and Coolant Dispenser.*



SE50-300TW Extra Power Sumpcleaner/Filter.

**Caution:** Machines must not be used for flammable fluids (fuels, paints, solvents, etc.) Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc.)



F50 - 5 Cubic Foot Filter

## F50 - 5.0 Cubic Foot Filter

The CECOR Extra Power Sumpcleaner has an extra capacity filter, the F50. The filter consists of a perforated metal outer basket with a polypropylene mesh liner sleeve. The sleeve provides a continuous filter, unbroken by slits or openings which can leak solids into the coolant. Filter also features a built-in lifting bail, anti-bridging reverse tapered sides and patented positive locking latch. Fittings for fork lift handling are integral to the two-piece cover. The F50 filter is standard on all SE50 units.

**Tank Size:** 175, 300, 400, 500 and 600 gallon capacity.

**Motor:** 5 HP Electric Motor  
Volts 208-230/460  
Amps 14.8-14.0/7.0  
Hertz 60  
Phase 3

**Pump:** Lobe Type, Positive Displacement air pump.

**Pumping Rate:** Up to 110 gallons per minute.

**Suction Lift:** 13" Hg (Mercury) or 177" water.

**Pressure Discharge:** 6 PSI (pounds per square inch) with safety backup valve.

**Filter:** F50 Filter has 5 cu. ft. capacity. Can hold up to 800 lbs. Features built-in lifting bail, anti-bridging reverse tapered sides and patented positive locking latch.

**Filter Sleeve:** Available in regular and fine polypropylene sleeves.

**Spill Prevention:** Automatic overflow control. All discharge ports valved.



SE50-300TW Extra Power Sumpcleaner/Filter.

**Hose:** 2" I.D. x 16' oil-resistant PVC hose including quick-disconnect coupler and suction tools. Separate return hose of heavy-section clear plastic 1 1/4" I.D. x 16' with full-flow shut-off nozzle.

**Cleaning Tools:** Flared Nozzle  
Flexible Nozzle  
Straight Nozzle

**Power Cord:** 15 feet standard  
50 feet available

See page 33 for information on base options.

**Options**

Model Number	Tank Size	Cleanout Door	Transport	Wheels	Dimensions	Shipping Weight	TW Base	PL6 Base	PM Base	CB1 Base	CB2 Base	CB3 Base	CB4 Base	CB5 Base	F23 Filter	Floor Squeegee	
SE50-175PT	175 gallon	8" x 10" with a 1 1/4" drain port	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	80" long 34" wide 61" high	1175 lbs.	X	X	X	X	X	X	X	X	X	X	
SE50-300TW	300 gallon	16" diameter hinged door with a 2 1/2" drain port.			TW Base- Tow Bar with pintle-eye hitch to accommodate most in-plant tugs or tractors.	96" long 42" wide 69" high	1454 lbs.	X	NA	X	X	X	X	X	X	X	X
SE50-400TW	400 gallon		99" long 46" wide 75" high	1860 lbs.		S	NA	X	X	X	X	X	X	X	X	X	X
SE50-500TW	500 gallon		111" long 48" wide 77" high	1945 lbs.		S	NA	X	X	X	X	X	X	X	X	X	X
SE50-600CB1	600 gallon			Not applicable.	121" long 42" wide 67" high	2039 lbs.	NA	NA	NA	X	X	X	X	X	X	X	

NOTE: Engineering specifications subject to change without notice.



102 Lincoln St. Verona, WI 53593 1-800-356-9042 Fax: 608-845-6792  
E-mail: cecor@cecor.net Website: www.cecor.net